# EAST Search History

| Ref # | Hits | Search Query | DBs | Default Operator | Plurals | Time Stamp |
|---|---|---|---|---|---|---|
| L1 | 1 | "20050232191" | US-PGPUB; USPAT | OR | ON | 2007/04/18 15:24 |
| L2 | 1 | "20050044242" | US-PGPUB; USPAT | OR | ON | 2007/04/18 15:25 |
| L3 | 1 | "7000189".pn. | US-PGPUB; USPAT | OR | ON | 2007/04/18 15:25 |
| S1 | 88122 | gateway or proxy adj server | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2006/12/06 17:55 |
| S2 | 20637 | S1 same (context or table or database or map) | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2006/12/06 17:58 |
| S3 | 11803 | S1 with (context or table or database or map) | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2006/12/06 18:02 |
| S4 | 6534 | S3 and (@ad<"20020711" or @pd<"20020711") | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2007/04/17 09:17 |
| S5 | 372 | proxy adj server with (context table map) and (@ad<"20020711" or @pd<"20020711") | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2006/12/06 18:06 |
| S6 | 285 | proxy adj server with (table map) and (@ad<"20020711" or @pd<"20020711") | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2006/12/06 18:07 |

| S64 | 58 | ("5341477" \| "5459837" \| "5475813" \| "5613155" \| "5655081" \| "5715453" \| "5742768" \| "5761507" \| "5774660" \| "5774668" \| "5781449" \| "5848270" \| "5867706" \| "5870559" \| "5881238" \| "5894554" \| "5903757" \| "5917491" \| "5933490" \| "5933596" \| "5933606" \| "5940594" \| "5951643" \| "5954798" \| "5956716" \| "5958008" \| "5958016" \| "5964836" \| "5974441" \| "5974462" \| "5974572" \| "6006260" \| "6006264" \| "6014437" \| "6016504" \| "6021439" \| "6023722" \| "6026414" \| "6035323" \| "6035332" \| "6037935" \| "6041041" \| "6052718" \| "6094659" \| "6098093" \| "6101508" \| "6108300" \| "6122658" \| "6128279" \| "6148335" \| "6182139" \| "6185601" \| "6240454" \| "6279001" \| "6314463" \| "6317786" \| "6381242" \| "6405252").PN. OR ("6912534").URPN. | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/13 09:29 |
|---|---|---|---|---|---|---|
| S65 | 21 | S64 and request with (append or appending or add or adding or addition or modify or modifying or extract or extracting or remove or removing) | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/13 09:51 |
| S66 | 1 | S64 and request with (append or appending or add or adding or addition or modify or modifying or extract or extracting or remove or removing) and http adj header | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/13 09:57 |
| S67 | 4151646 | @ad<"20020711" or @rlad<"20020711" | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/13 09:58 |
| S68 | 4812 | S67 and web adj page and http and request with (append or appending or add or adding or addition or modify or modifying or extract or extracting or remove or removing) | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/13 10:00 |

| S69 | 375 | S67 and http and web adj page with request with (append or appending or add or adding or addition or modify or modifying or extract or extracting or remove or removing) | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/13 10:01 |
|-----|-----|-----|-----|-----|-----|-----|
| S70 | 144 | S67 and http and web adj page with request near4 (append or appending or add or adding or addition or modify or modifying or extract or extracting or remove or removing) | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/13 10:11 |
| S71 | 0 | S67 and http and web adj page with request near4 (append or appending or add or adding or addition or modify or modifying or extract or extracting or remove or removing) with token | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/13 10:12 |
| S72 | 25 | S67 and http and web adj page with request near4 (append or appending or add or adding or addition or modify or modifying or extract or extracting or remove or removing) with information | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/13 10:12 |
| S73 | 1 | "20060031417" | US-PGPUB; USPAT | OR | ON | 2007/04/17 09:13 |
| S74 | 6 | service near2 availab$6 near3 header | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2007/04/17 09:15 |
| S75 | 693 | load near2 balanc$5 same header | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2007/04/17 09:15 |
| S76 | 33293590 | (@ad<"20020711" or @pd<"20020711") | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2007/04/17 09:17 |

| | | | | | | |
|---|---|---|---|---|---|---|
| S77 | 395 | S75 and S76 | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2007/04/17 09:18 |
| S78 | 146 | S77 and "709"/$.ccls. | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2007/04/17 09:20 |
| S79 | 72 | S78 and prox$3 | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2007/04/17 09:27 |
| S80 | 2 | "20020049842" | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2007/04/17 09:32 |
| S81 | 2 | "6839700".pn. | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2007/04/17 09:32 |
| S82 | 8 | ("6128279" \| "6279001" \| "6314463" \| "6317786" \| "6405252" \| "6484143" \| "6629127").PN. OR ("6839700").URPN. | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/17 10:36 |
| S83 | 0 | "09969294".pn. | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/17 10:37 |
| S84 | 1 | offloading adj application adj components adj edge.ti. | US-PGPUB; USPAT; USOCR | OR | ON | 2007/04/17 13:21 |
| S86 | 1 | "20030101278" | US-PGPUB; USPAT | OR | ON | 2007/04/18 15:22 |
| S87 | 1 | "20040215665" | US-PGPUB; USPAT | OR | ON | 2007/04/18 15:23 |

*OS    04/17/07*

## Google

Web   Images   Video   News   Maps   more »

"service-availability: " request http header    [ Search ]   Advanced Search
Preferences

**Web**         Results 1 - 100 of about 47,700 for "service-availability: " request http header. (0.25 seconds)

### CSS Content Load-Balancing Configuration Guide (Software Version ...
The CSS examines the **HTTP header** and URL in the **HTTP request** method (for example,
GET, ... based on content rules, load balancing, and **service availability**. ...
www.cisco.com/en/US/products/hw/contnetw/
ps792/products_configuration_guide_chapter09186a008029c992.html - 34k -
Cached - Similar pages

### Integrate the Network With .NET
They might use **HTTP** as the transport, such as with SOAP/XML, ... on how to direct that
client **request** might not be found in the URL or the **HTTP header**. ...
www.f5.com/communication/articles/archive00/article120203.html - 36k -
Cached - Similar pages

### White Paper - The Impact of Web Services on the Network
Key systems and devices that ensure Web **service availability** and reliability will be
required ... **HTTP::header** sanitize "ETag" "Content-Type" "Connection" ...
www.f5.com/solutions/technology/webservices_wp.html - 55k - Cached - Similar pages
[ More results from www.f5.com ]

### Best Practices for Web services, Part 10: Web Services performance ...
For example, defined in the SOAP specification is the SOAPAction **HTTP header** in the
**request**, which **HTTP** proxy servers use to dispatch requests to particular ...
www.ibm.com/developerworks/webservices/library/ws-best10/ - 45k -
Cached - Similar pages

### SOA realization: Service design principles
The SOA infrastructure offers runtime service location and **request** routing mechanisms.
Availability, Individual **service availability** characteristics should ...
www.ibm.com/developerworks/webservices/library/ws-soa-design/ - 82k -
Cached - Similar pages

### Http Monitor Software
HTTProbe is a powerful **HTTP** viewer and analyser written in Java which allows you to read
**HTTP headers**, log them and resend directly a **HTTP request** sent from ...
www.programurl.com/software/**http**-monitor.htm - 80k - Cached - Similar pages

### Setting Connection Timeouts to Save Resources (IIS 6.0)
Use the HeaderWaitTimeout metabase property to set a **request** timeout for the ... the client
computer to send all **HTTP headers** for a **request** (indicated by a ...
www.microsoft.com/technet/prodtechnol/windowsserver2003/library/IIS/31a2f39c-4d59-
4cba-905c-60e7af657e49.mspx - 16k - Cached - Similar pages

### System Monitoring with the Exchange Management Pack
Outlook Web Access logon failure: (**HTTP** error 400) Bad **Request** This rule ... server
security from being compromised by examining **HTTP header** information and ...
www.microsoft.com/technet/mom/2005/library/exchpack/empformom2005_5.mspx - 87k -
Cached - Similar pages
[ More results from www.microsoft.com ]

### SOA Monitoring

**Google**

Web   Images   Video   News   Maps   **more »**

add "http request header" proxy

[ Search ]   Advanced Search
              Preferences

**Web**   Results **31 - 40** of about **30,200** for add "http request header" proxy. (0.36 seconds)

### Http request error when using AJAX.
**Proxy**-Authorization: Basic cnBqYW5ha2E6YTdoMzEkNW0= Pragma: no-cache ... BTW:
Did you try sending the Content-Length **HTTP Request Header**? xmlHttp. ...
www.daniweb.com/techtalkforums/thread73229.html - 64k - Cached - Similar pages

### iAnywhere.com - CREATE PROCEDURE statement
AT location-string clause Create a **proxy** stored procedure on the current ... use this clause
to modify **HTTP request header** entries, or to **add** new ones. ...
www.ianywhere.com/.../product_manuals/sqlanywhere/1000/en/html/dbrfen10/rf-create-
procedure-statement.html - 29k - Cached - Similar pages

### SecurityFocus
Forcing the first **proxy** server in the chain to respond to the TRACE request (rather than
forward it) is as simple as including an **HTTP request header** ...
www.securityfocus.com/archive/1/423028 - 16k - Cached - Similar pages

### Client-side state with HTTP cookies.
SYNTAX OF THE COOKIE **HTTP REQUEST HEADER** When requesting a URL from an
HTTP ... When caching HTTP, as a **proxy** server might do, the Set-cookie response ...
www.infospheres.caltech.edu/mailing_lists/java/msg00016.html - 15k -
Cached - Similar pages

### GskHttpRequest
**Add** Accept-CharSet headers to the header. The char-sets will be freed when ... **Proxy**-
Authorization is intended to provide access control to the **proxy**. ...
gsk.sourceforge.net/gsk-reference/GskHttpRequest.html - 53k - Apr 16, 2007 -
Cached - Similar pages

### Configuring Transport-Level Security
The steps for configuring transport-level custom credentials are described in "**Adding** a
**Proxy** Service" under **Proxy** Services in Using the AquaLogic Service ...
edocs.bea.com/alsb/docs26/security/transport_level.html - 58k - Cached - Similar pages

### draft duerst query i18n 00 txt
Transcoding Server/**Proxy**: A HTTP Server or **Proxy** which transcodes the documents it
serves, to respond to an "Accept-Charset" **HTTP request header** field. ...
gbiv.com/protocols/uri/drafts/draft-duerst-query-i18n-00.txt - 16k - Cached - Similar pages

### A Service-Oriented Architecture for Enabling Centralized ...
The **proxy** servlet filter parameters define the URL for the application domain. Servlet Filter
The servlet filter modifies the **HTTP request header** to add a ...
dev2dev.bea.com/pub/a/2004/09/ssosaml.html - 64k - Cached - Similar pages

### Internet Access Monitor: Configuring the ISA Server 2006 HTTP Filter
This example shows the request type (GET), the **HTTP request Header** (HTTP/1.1) the
User-Agent ... Works with Microsoft ISA Server and other **proxy** servers ...
www.internetaccessmonitor.com/.../Configuring-ISA-Server-2006-HTTP-Filter.php - 26k -
Cached - Similar pages

### Log Files - Apache HTTP Server